



**High Power Current Sensing Resistors RLP Series
(Halogen-Free)
AEC-Q 200-Ver D qualified**

Document No	TRLP-250S011C
Issued date	2016/10/11
page	1/6

1. Scope :


This specification applied to the products of current sensing resistor of metal foil for Lead-Free RLP series manufactured by TA-I TECHNOLOGY CO.,LTD.

2. Type Designation :


<u>R</u> <u>L</u> <u>P</u> Item	<u>2</u> <u>5</u> Series No.	<u>E</u> Resistance tolerance	<u>E</u> Packaging	<u>C</u> Power rating	<u>M</u> Metal	<u>R</u> <u>0</u> <u>1</u> <u>0</u> Resistance
	25:2512 (6432)	F:±1% G:±2% J:±5%	E: Embossed Tape	C=1W D=1.5W E=2W G=3W	M=Mn/Cu	e.g : R010=10mΩ

3. Construction and Dimension :

3.1 Construction:



3.2 Dimension:



Unit : mm

Style	L	W	C	T	Material
RLP25	6.4±0.2	3.2±0.2	2.0±0.2(≤4mΩ)	0.7 ±0.20	Strip : Alloy Over Coating : molding Compound UL-94V-0 grade
			0.9±0.2(R>4mΩ)		



**High Power Current Sensing Resistors RLP Series
(Halogen-Free)
AEC-Q 200-Ver D qualified**

Document No	TRLP-250S011C
Issued date	2016/10/11
page	2/6

4. Features:

Type	RLP25
Power Rating	$1\text{ m}\Omega \leq R \leq 60\text{m}\Omega$ (1W、1.5W、2W、3W)
Resistance Value	$1\text{ m}\Omega \sim 60\text{m}\Omega$
Operation Temperature Range	$-55^{\circ}\text{C} \sim +170^{\circ}\text{C}$
Temperature Coefficient of Resistance	$\pm 50\text{ppm}/^{\circ}\text{C}$
Tolerance	$\pm 1\%, \pm 2\%, \pm 5\%$
Insulation Resistance	Over 100M Ω
Maximum Working Current(I)	$(P/R)^{1/2}$


Note:2&3watts total Solder pad and trace size of 300mm

5. Reliability Tests :

Test Items	Reference	Condition of Test	Test Limits
Temperature Coefficient of Resistance	IEC60115-1 4.8	$+25 \sim 125^{\circ}\text{C}$	Refer 4.0
High Temperature Exposure(Storage)	MIL-STD-202 Method 108	T= 125°C , 1000hrs, Measurement at 24hrs after test conclusion.	$< \pm 1\%$
Low temperature operation	IEC60115-1 4.23.4	-55°C for 45 min	$< \pm 0.5\%$
Temperature Cycling	JESD22 Method JA-104	1000Cycle (-55°C to 125°C), Measurement at 24hrs after test conclusion.	$< \pm 0.5\%$
Short time overload	IEC60115-1 4.13	5 X rated power for 5s	$< \pm 0.5\%$
Biased Humidity	MIL-STD-202 Method 103	10% Rated voltage at 85°C , RH:85% ,1000Hrs, Measurement at 24hrs after test conclusion.	$< \pm 0.5\%$
Operation life	MIL-STD-202 Method 108	1000 h at $+70^{\circ}\text{C}$, 1.5 h "ON", 0.5 h "OFF"	$< \pm 1\%$
Resistance to Soldering Heat	IEC60115-1 4.18	T= $260 \pm 5^{\circ}\text{C}$ solder, 10 ± 1 sec dwell	$< \pm 0.5\%$
Mechanical Shock	MIL-STD-202 Method 213	100g's , Normal duration is 6ms , half sine shock pulse	$< \pm 0.5\%$
Resistance to vibration	MIL-STD-202 Method 204	5g's for 20min.12cycles, 10-2000Hz	$< \pm 0.5\%$
Board Flex	AEC-Q200-005	Min 2mm deflection ,60sec.	$< \pm 0.5\%$
Flammability	UL-94	V-0 or V-1are acceptable, Electrical test not required	



5.1 Derating Curve



5.2 Rated Current

The rated voltage is calculated by the following Formula:


$$I = \sqrt{P \div R}$$

I: Rated Current(I)

P: Rated Power(W)

R: Resistance Value(Ω)

6. Recommended Solder Pad Dimension



Resistance Range (Ω)	a	b	L
R > 0.004	4.0	2.1	4.1
R ≤ 0.004	4.0	3.1	1.3

Unit: mm




High Power Current Sensing Resistors RLP Series
(Halogen-Free)
AEC-Q 200-Ver D qualified

Document No	TRLP-250S011C
Issued date	2016/10/11
page	4/6


7. Number of Package:

4000 Pieces / package

8. Label:



9. Taping




Packing	Type	A	B	W	F	E	P ₁	P ₂	P ₀	D ₀	t
Emboss	RLP25	3.6±0.2	6.9±0.2	12.±0.2	5.5±0.05	1.75±0.1	4.0±0.1	2.0±0.05	4.0±0.05	$\phi 1.5$ (+0.1/-0)	1.2±0.15



High Power Current Sensing Resistors RLP Series
(Halogen-Free)
AEC-Q 200-Ver D qualified

Document No	TRLP-250S011C
Issued date	2016/10/11
page	5/6


10. Reel Specification



Series	ϕA	ϕB	ϕC	W	T
RLP 25	180 ⁺⁰ ₋₃	60 ±1.0	13.0±1.0	13.0±1.0	15.4±2.0

11. Peeling Strength of Top Cover Tape

Test Condition: 0.1 to 0.7 N at a peel-off speed of 300 mm / min.



12. Storage Conditions:

Temperature: 5°C ~35°C, Humidity: 40%~75%

13. Shelf Life:


2 years from manufacturing date.



**High Power Current Sensing Resistors RLP Series
(Halogen-Free)
AEC-Q 200-Ver D qualified**

Document No	TRLP-250S011C
Issued date	2016/10/11
page	6/6

14. Recommend IR – Reflow profile: (solder: Sn96.5 / Ag3 / Cu0.5)



Peak : $260 \begin{matrix} +5 \\ -0 \end{matrix}$ °C , 5 sec

Pre – heat zone : 150 to 180 °C, 90 ± 30 sec

Soldering zone : 230°C or higher , 30 ± 10 sec

Iron Solder: 350 ± 10 °C , 3+1/-0 sec

15. ECN

Engineering Change Notice: The customer will be informed with ECN if there is significant modification on the characteristics and materials described in approval sheet.

16. Manufacturing Country & City :

TA-I TECHNOLOGY CO., LTD. (Taiwan– Tao Yuan)

Tel: (+886) 3-3246169 Fax : (+886) 3-3246167

Associated companies :

(1)TA-I TECHNOLOGY (SU ZHOU) CO., LTD. (China – Su Zhou)

Tel :(+86) 512-63457879 Fax : (+86) 512-63457869

(2) TA-I TECHNOLOGY ELECTRONIC (DONGGUAN) CO., LTD. (China –Dongguan)

Tel : (+86) 769-8339-4790~3 Fax : (+86) 769-8339-4794

(3) FORTUNE TASK RESISTOR FACTORY (China – Dongguan)

Tel : (+86) 769-8339-4790~3 Fax : (+86) 769-8339-4794

(4) TAI OHM ELECTRONICS (M) SDN. BHD. (Malaysia – Penang)

Tel :(+60) 4- 3900480 Fax : (+60) 4-3901481

(5) P.T.TAI ELECTRONIC Indonesia (Indonesia – Jakarta)

Tel :(+62) 21-44820254 Fax : (+62) 21-44820256